

AMENDMENTS TO THE CLAIMS

Please amend the claims as follows. This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims

1 – 16 (Cancelled)

17. (Currently amended) An electrostatic spraying device comprising:
a high voltage generator having a high voltage output;
at least one dispensing nozzle configured to release electrostatically sprayable material during spraying operations;
a housing enclosing at least one reservoir configured to store materials to be sprayed;
a tube connecting the at least one dispensing nozzle and the at least one reservoir, the tube configured to convey the materials to be sprayed from the at least one reservoir to the at least one dispensing nozzle;
means coupling the high voltage output of the high voltage generator to the materials so that the voltage is conducted through the materials to the materials present at the at least one dispensing nozzle;
at least one ring surrounding the at least one dispensing nozzle, the at least one ring coupled to the high voltage generator, the at least one ring configured

to develop a high voltage of the same polarity as that applied to the materials being sprayed and to generate an electric field in the vicinity of the at least one dispensing nozzle;

wherein the development of a high voltage by the at least one ring of the same polarity as that applied to the materials being sprayed and the generation of an electric field in the vicinity of the at least one dispensing nozzle by the at least one ring during spraying operations causes the electrostatic spraying device ~~is configured~~ to impart an electrostatic charge to the materials issuing from the at least one nozzle and to focus the material being sprayed when a forward extremity of the ring is brought in proximity to an earthed target to be sprayed.

18. (Previously presented) The electrostatic spraying device of claim 17 wherein the at least one dispensing nozzle is mounted in fixed relation to the housing enclosing the at least one reservoir and the at least one ring is in the form of an annular cable mounted on the housing enclosing the at least one reservoir in substantially concentric relation with the at least one dispensing nozzle.

19. (Previously presented) The electrostatic spraying device of claim 17 further comprising means for supplying the materials to the at least one dispensing nozzle passively.

20. (Previously presented) The electrostatic spraying device of claim 17 further comprising pumping means for supplying the material to the at least one dispensing nozzle by a user-induced operation.

21. (Currently amended) The electrostatic spraying device of claim 17 wherein the electrostatic spraying device during spraying operations is further configured to generate an iontophoresis effect to enhance material transport through a skin of an earthed target to be sprayed when the forward extremity of the at least one nozzle is within a distance of 2 cm of the skin of the earthed target.

22. (Currently amended) The electrostatic spraying device of claim 18 wherein the at least one ring comprises, at least in part, an electrically semi-insulating material which is coupled to the source of high voltage, the electrically semi-insulating material having sufficient conductivity to permit a potential to be established at a location in front of the at least one nozzle which is of the same polarity as that applied to the material issuing from the at least one nozzle during spraying operations.